

nowox.cn nowoxled.com








Dimension 200mm 250mm 300mm 350mm

System Diagram



DMX Sphere - BM200/250/300/350

RGBW

This DMX Sphere can be suspended from the ceiling vertically in stage, events, theme park and so on. Lighting effects can be seen from 360degree.


Apply solid capacitor and other good brand components on PCB for long life time. Save 40% power with more efficient power management design.

With wide voltage range design, LED color always keep same brightness after long distance power supply. Standard DMX512 control protocol (Max 44frames/second).

The communication between balls is synchronized perfectly under support of Nowox Led Artnet Controller. Lightning and ESD Protection

Electrical Protections: short circuit, over current, over voltage and over temperature.

Models LED	BM200	BM250	ВМ300	ВМ350
Color	RGBW Rad Green Base Wilde	RGBW and Green Day Wilds	RGBW and Green than 1993a	RGBW Itel Creen Blast White
Light Source	CREE High Power LE	D		
Color	R:619-624nm G:520-535nm B:460-475nm W:3000K/4000K/60	000K		
LED QTY	6LEDs			
Performance				
Lumen Output	187lm			
Efficacy	44lm/W			
Beam Angle	360° Opal Cove	r		
Electrical				
Input Voltage	24VDC			
Power Consumption	5W			
Control				
Protocols	DMX512 Control			
PWM Frequency	16Bit			
Addressing	Manual Addressin	g with Nowox Led A	ddressing Tool C	D-MT512
Pixels	1Pixels			
Physical				
Material	PE			
Cover	Opal			
Diameter	Ф200mm/250mm/	300mm/350		
Cable Entry	Top Entry			
Mounting	Suspended			



Dimension System Diagram NO.1 NO.1 NO.1 NO.1 NO.1 NO.1 NO.1 IP67 Connector to XLR 5PIN Cable

DMX 3D Clear Tube - TC100


RGB

This DMX 3D Clear Tube can be suspended from the ceiling horizontally and vertically in club, stage, events and so on. Double side lighting effects can be seen from 360 degree.

2D pixel mapping can be transformed to be 3D with the help of software programming.


Models LED	TC050	TC100	TC150	TC200
Color	RGB food Green Store	RGB And Gream Bar	RGB ford Green Blase	RGB ted Graves Base
Light Source	Epistar	Epistar	Epistar	Epistar
Color	R:620-630nm	R:620-630nm	R:620-630nm	R:620-630nm
	G:520-530nm	G:520-530nm	G:520-530nm	G:520-530nm
	B:460-470nm	B:460-470nm	B:460-470nm	B:460-470nm
LED QTY	48LEDs	96LEDs	144LEDs	192LEDs
Performance				
Lumen Output	187lm	375lm	562lm	750lm
Efficacy	44lm/W	44lm/W	44lm/W	44lm/W
Beam Angle	360° Clear Cove	r		
Electrical				
Input Voltage	24VDC	24VDC	24VDC	24VDC
Power Consumption	5W	10W	15W	20W
Control				
Protocols	DMX512 Control	DMX512 Control	DMX512 Control	DMX512 Control
PWM Frequency	16Bit			
Addressing	Manual Addressing	g with Nowox Led A	ddressing Tool CD-	MT512
Pixels	8Pixels	16Pixels	24Pixels	32Pixels
Physical				
Material	PC			
Cover	Clear			
Diameter	Ф30mm			
Cable Entry	Top Entry			
Mounting	Suspended			
Length	500mm/1000mm/1	L500mm/2000mm		







System Diagram



DMX 3D Opal Tube - TM100

RGB

This DMX 3D opal tube can be suspended from the ceiling horizontally and vertically in club, stage, events and so on. Double side lighting effects can be seen from 360degree.

2D pixel mapping can be transformed to be 3D with the help of software programming.

Models LED	TM050	TM100	TM150	TM200
Color	RGB ted Caree Bur	R _{GB}	RGB had Green Bus	RGB ted Green Blue
Light Source	Epistar	Epistar	Epistar	Epistar
Color	R:620-630nm	R:620-630nm	R:620-630nm	R:620-630nm
	G:520-530nm	G:520-530nm	G:520-530nm	G:520-530nm
	B:460-470nm	B:460-470nm	B:460-470nm	B:460-470nm
LED QTY	60LEDs	120LEDs	180LEDs	240LEDs
Performance				
Lumen Output	208lm	415lm	622lm	830lm
Efficacy	29lm/W	29lm/W	29lm/W	29lm/W
Beam Angle	360° Opal Cover	-		
Electrical				
Input Voltage	24VDC	24VDC	24VDC	24VDC
Power Consumption	7.5W	15W	22.5W	30W
Control				
Protocols	DMX512 Control	DMX512 Control	DMX512 Control	DMX512 Control
PWM Frequency	16Bit			
Addressing	Manual Addressing	g with Nowox Led A	ddressing Tool CD-	MT512
Pixels	10Pixels	20Pixels	30Pixels	40Pixels
Physical				
Material	PC			
Cover	Opal			
Diameter	Ф50mm			
Cable Entry	Top Entry			
Mounting	Suspended			
Length	500mm/1000mm/1	1500mm/2000mm		





















Dimension










System Diagram





Olympic DMX Panel- DP1201603

RGB

This DMX Panel is designed for Events, Stadium Games, Stage and so on. High-Brightness IPX6 SMD RGB LEDs are used on this panel. Apply solid capacitor and other good brand components on PCB for long life time.

Models LED	DP1201603
Color	R _{GB}
Light Source	Epistar LED
Color	R:619-624nm G:520-540nm B:460-480nm
LED QTY	16LEDs
Performance	
Lumen Output	88lm
Beam Angle	115°
Electrical	
Input Voltage	24VDC
Power Consumption	3W
Control	
Protocols	DMX512 Control
PWM Frequency	16Bit
Addressing	Auto Addressing
DMX Channels	3Channels
Physical	
Material	PC
Finish Color	Black
Optics	Open
Cable Entry	Bottom Entry
Dimensions (L X W X H)	120X120mm























Dimension



System Diagram




DMX Pixel Board - DP2506404 RGBW

This LED DMX Panel is designed for lighting box, backlight and so on. We used Top Brand Glue for better heatconduction, strong temperature withstand and perfect waterproof performance. Apply solid capacitor and other good brand components on PCB for long life time.

Models LED	DP2506404
Color	RGBW Ref Green State William
Light Source	Epistar LED
Color	R:619-624nm G:520-535nm B:460-475nm W:3000K/4000K/5700K
LED QTY	64LEDs
Performance	
Lumen Output	375lm
Beam Angle	115°
Electrical	
Input Voltage	24VDC
Power Consumption	10W
Control	
Protocols	DMX512 Control
PWM Frequency	16Bit
Addressing	Manual Addressing with Nowox Led Addressing Tool
Pixels	16Pixels
Physical	
Material	FR4 PCB Board
Finish Color	White
Optics	N/A
Cable Entry	Side Entry
Dimensions (L X W X H)	250X250mm






LED Wall Washer - W32


Static White


The Nowox Led W32 LED Washer is a IP54 rated exterior compact flex linear grazing luminaire with high output brightness. With modular splicing design, the irradiation angle can be adjusted by a single module, and the light distribution is complete.


Models LED	W320100301
Color	Static W hite
Light Source	High Power LED
Color	W:2700K W:3000K W:4000K W:5700K W:6500K
CRI for White LED	Ra>80
LED QTY	3LEDs per module
Performance	
Lumen Output	400lm
Beam Angle	15° 20° 30° 50° 20°X40°
Electrical	
Input Voltage	24VDC
Power Consumption	5W per module
Control	
Protocols	On-off PWM Dimmable
Physical	
Housing	Aluminum 6063 with Tempered Glass
Finish Color	Powder coating, Black/Grey Silver or Custom RAL Color
Dimensions (L X W X H)	100X32X62mm per module
Length	Max 10Modules @1000mm L
Cable Entry	Side Entry
Mounting	Surface Mounting
Accessory	Honey Comb Louver












System Diagram



LED Wall Washer - W26


Static White

The Nowox Led W26 LED Washer is a IP66 rated exterior compact linear grazing luminaire with high output brightness.

Models LED	W261002401
Color	Static W hite
Light Source	Mid Power LED
Color	W:2700K W:3000K W:4000K W:5700K W:6500K
CRI for White LED	Ra>80
LED QTY	24LEDs per meter
Performance	
Lumen Output	100lm/W based at 4000K
Beam Angle	20° 40° 23°X40°
Electrical	
Input Voltage	24VDC
Power Consumption	24W/Meter
Control	
Protocols	On-off PWM Dimmable
Physical	
Housing	Aluminum 6063 with Tempered Glass
Finish Color	Powder coating, Black/Grey Silver or Custom RAL Color
Dimensions (L X W X H)	1000*26*55mm
Length	500mm/1000mm 305mm/1220mm
Cable Entry	Bottom Entry
Mounting	Surface Mounting

Light On/Off DMX resistant

Dimension



DMX IN

-15-

DMX Signal

LED Wall Washer - W36

Static White/RGBW

The Nowox Led W36 LED Washer is a IP66 rated exterior compact linear grazing luminaire with high output brightness.

Product Specification

Models LED	W361002401	W361002404
Color	Static W hite	RGBW Rad Green Blue White
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:619-624nm G:520-535nm B:460-475nm W:3000K/4000K/5700K
CRI for White LED	Ra>80	Ra>80
LED QTY	24LEDs per meter	24pcs RGBW 4IN1 LEDs

Performance

Lumen Output	2880lr	n				1900lı	m		
Efficacy	80lm/\	N based	at W300	00K		52lm/	W based a	t W3000K	
Beam Angle	10°	20°	30°	45°	15°X40°	15°X60°	20°	20°X35°	

Electrical

Input Voltage 24VDC 24VDC	
Power Consumption 36W per meter 36W per m	neter


Control


Protocols	Light On-off or PWM or DMX	DMX
Addressing	Manual Addressing with Nowox Led A	ddressing Tool
Piyels	1Pixel	4Pixels

Physical

1 Hysicai	
Housing	Aluminum 6063 with Tempered Glass
Finish Color	Powder coating, Black/Grey Silver or Custom RAL Color
Cable Entry	Bottom Entry
Dimensions (L X W X H)	1000*36*32mm (exclude brackets) 1000*55*67mm (include brackets)
Mounting	Surface Mounting
Length	500mm/1000mm/305mm/1220mm


-16-





System Diagram

-17-



LED Wall Washer - W48


Static White

The Nowox Led W48 LED Washer is a IP66 rated exterior middle size linear grazing luminaire with high output brightness.

Models LED	W480601201	W480901801	W481002401	W481202401		
Color	Static W hite	Static W hite	Static W hite	Static W hite		
Light Source Color	High Power LED 2700K 3000K 4000K 5700K 6500K	High Power LED	High Power LED	High Power LED		
CRI for White LED	Ra>80					
LED QTY	12LEDs	18LEDs	24LEDs	24LEDs		
Performance						
Lumen Output	1680lumen	2520lumen	3360lumen	3360lumen		
Efficacy	70lm/W based	d at 3000K				
Beam Angle	10° 20°	30° 45° 1	5°X40° 15°X60°			
Electrical						
Input Voltage	120-277VAC					
Power Consumption	on 24W	36W	48W 4	18W		
Control						
Protocols	Light On-off / [DALI2 / 0-10V / TRIA				
Addressing	N/A					
Pixels	N/A					
Physical						
Material	Aluminum 606	3 with Tempered Glas	SS			
Finish Color	Powder coating	, Black/Grey Silver or	Custom RAL Color			
Cable Entry	Bottom Entry					
Dimensions (L X W X H)		609/913.5/1000/1218X48X68.5mm (exclude brackets) 609/913.5/1000/1218X48X90mm (include brackets)				
Mounting	Surface Mounti	ing				
Accessory	Half Glare Shie	ld				
Length	609mm/913.5	mm/1000mm/1218i	mm			

120-277 VAC Power RDM Con/Off Pesistant IP67 Society Rohs Warranty years

Dimension




LED Wall Washer - W48

RGBW Quad

The Nowox Led W48 LED Washer is a IP66 rated exterior middle size linear grazing luminaire with high output brightness.

Models LED	W480601204	W480901804	W481002404	W481202404
Color	RGBW tad Green Sian White	RGBW Red Green Share White	RGBW Red Green Blaut White	RGBW tad Green Slaw White
Light Source	High Power LED	High Power LED	High Power LED	High Power LED
Color	RGBW 4in1	R:618-628 G:525-535 B:465-475 W:3000K/4	nm	
CRI for White LED	Ra>80			
LED QTY	12LEDs	18LEDs	24LEDs	24LEDs
Performance				
Lumen Output	1200lumen	1800lumen	2400lumen	2400lumen
Efficacy	Efficacy50lm/	W based at 3000K		
Beam Angle	20° 20°X35	0		
Electrical				
Input Voltage	120-277VAC			
Power Consumption	on 24W	36W	48W 4	-8W
Control				
Protocols	DMX 512			
Addressing	Manual addres	sing with CD Address	sing Tool	
Pixels	1Pixel (1Pixel p	er fitting)		
Physical				
Material	Aluminum 606	3 with Tempered Gla	SS	
Finish Color	Powder coating	g, Black/Grey Silver o	r Custom RAL Color	
Cable Entry	Bottom Entry			
Dimensions (L X W X H)		00/1218X48X68.5m 00/1218X48X90mm	im (exclude brackets) i (include brackets)	
Mounting	Surface Mount	ing		
Accessory	Half Glare Shie	eld		
Length	609mm/913.5	mm/1000mm/1218	mm	





LED Wall Washer - W48

RGBW Discrete

The Nowox Led W48 LED Washer is a IP66 rated exterior middle size linear grazing luminaire with high output brightness.

Product Specification

Models LED	W480602404	W480903604	W481004004	W481204804
Color	RGBW and Green Start White	RGBW Red Green Blast White	RGBW test Green Black Whites	RGBW ted Green than White
Light Source	High Power LED	High Power LED	High Power LED	High Power LED
Color		R:620-630r	nm	

RGB(Royal Blue)W

G:520-535nm B:450-465nm

W:Amber/PC Amber/2700K/3000K/4000K/5700K/6500K

CRI for White LED	Ra>80			
LED QTY	24LEDs	36LEDs	40LEDs	48LEDs
Performance				
Lumen Output	1200lumen	1800lumen	2400lumen	2400lumen
Efficacy	Efficacy50lm/	W based at 3000K		
Beam Angle				

	10°	20°	30°	45°	15°X40°	15°X60°		
Electrical								
Input Voltage	120-277	7VAC						
Power Consumption	24W		36W		48\	V	48W	
Control								
Protocols	DMX 51	2						
Addressing	Manual	Nanual addresing with CD Addressing Tool						
Pixels	1Pixel (1	Pixel (1Pixel per fitting)						
Physical								
Material	Aluminu	ım 6063	with Ten	npered G	Slass			
Finish Color	Powder	coating,	Black/Gr	ey Silver	or Custor	m RAL Colo	r	
Cable Entry	Bottom	Entry						
Dimensions	609/91	3.5/1000	0/1218X	48X68.5	5mm (exc	lude bracke	ets)	
(LXWXH)	609/91	3 5/1000	1/1218Y	48 Y 90m	nm (includ	e hrackets)		

609/913.5/1000/1218X48X90mm (include brackets)

609mm/913.5mm/1000mm/1218mm


Surface Mounting

Half Glare Shield

Mounting

Accessory

Length





LED Spot Light -SPH60


RGBA/RGBW

The Nowox Led SL60 LED Spot Light is a IP66 rated exterior compact luminaire with high output brightness.

This is a favorite choice for residential and commercial spaces.

Models LED	SPH600104
Color	RGBA RGBW Rd Grave Bur White Rd Grave Bur White
Light Source	High Power LED
Color	RGBA / RGBW
CRI for White LED	Ra>80
LED QTY	1pc RGBW 4IN1 LEDs
Performance	
Lumen Output	384lm
Efficacy	32lm/W
Beam Angle	8°
Electrical	
Input Voltage	24DC
Power Consumption	12W
Control	
Protocols	DMX512
Addressing	Manual addresing with CD Addressing Tool
Physical	
Housing	6063 high density extruded aluminium alloy
Lens	4mm Tempered Glass
Finish	Powder coating, Black/White/Grey or Custom RAL Color
Dimensions (L X W X H)	155x60x110mm
Cable Entry	Bottom Entry
Mounting	Surface Mounting








Accessories

-25-





LED Spot Light -SP60

Static White/RGBW


The Nowox Led SP is a DC or AC Version exterior luminaire to light the facades, walls, and landmarks with powerful color washer effects.

This floodlight is available in Warm White (3000K), Neutral White (4000K) or Cold White (5700K) and RGBW 4IN 1.

Apply solid capacitor and other good brand components on PCB for long life time.


Models LED	SP600301	SP600304	
Color	Static W hite	RGBW Red Green that white	
Light Source	High Power LED	High Power LED	
Color	2700K 3000K 4000K 5700K 6500K	R:618-628nm G:525-535nm B:465-475nm W:3000K/4000K/6500K	
CRI for White LED	Ra>80	Ra>80	
LED QTY	3LEDs	3pcs RGBW 4IN1 LEDs	
Performance			
Lumen Output	630lm	450lm	
Efficacy	70lm/W based at W3000K	50lm/W based at W3000K	
Beam Angle	15° 25° 40° 60°	25° 40° 60°	
Electrical			
Input Voltage	120-277VAC	24VDC	
Power Consumption	9W	9W	
Control			
Protocols	Light On-off	DMX	
Addressing	N/A Manual	addresing with CD Addressing Tool	
Physical			
Housing	6063 high density extruded aluminium	alloy	
Lens	4mm Tempered Glass		
Finish	Powder coating, Black/White/Grey or Custom RAL Color		
Dimensions (L X W X H)	60x100x152mm		
Cable Entry	Bottom Entry		
Mounting	Surface Mounting		







Accessories





LED Spot Light -SP80

Static White/RGBW


The Nowox Led SP is a DC or AC Version exterior luminaire to light the facades, walls, and landmarks with powerful color washer effects.

This floodlight is available in Warm White (3000K), Neutral White (4000K) or Cold White (5700K) and RGBW 4IN 1.


Apply solid capacitor and other good brand components on PCB for long life time.

Models LED	SP800401	SP800404
Color	Static W hite	RGBW Ind Green Black White
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:618-628nm G:525-535nm B:465-475nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	4LEDs	4pcs RGBW 4IN1 LEDs
Performance		
Lumen Output	840lm	600lm
Efficacy	70lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	15° 25° 40° 60°	25° 40° 60°
Electrical		
Input Voltage	120-277VAC	24VDC
Power Consumption	12W	12W
Control		
Protocols	Light On-off	DMX
Addressing	N/A Ma	anual addresing with CD Smart addresser
Physical		
Housing	6063 high density extruded alun	ninium alloy
Lens	4mm Tempered Glass	
Finish	Powder coating, Black/White/Grey	or Custom RAL Color
Dimensions (L X W X H)	60x100x152mm	
Cable Entry	Bottom Entry	
Mounting	Surface Mounting	





Accessories







LED Spot Light -SP100


Static White/RGBW

The Nowox Led SP is a DC or AC Version exterior luminaire to light the facades, walls, and landmarks with powerful color washer effects.

This floodlight is available in Warm White (3000K), Neutral White (4000K) or Cold White (5700K) and RGBW 4IN 1.

Apply solid capacitor and other good brand components on PCB for long life time.

Models LED	SP1000601	SP1000604		
Color	Static White	RGBW tad Green Electricity		
Light Source	High Power LED	High Power LED		
Color	2700K 3000K 4000K 5700K 6500K	R:618-628nm G:525-535nm B:465-475nm W:3000K/4000K/6500K		
CRI for White LED	Ra>80	Ra>80		
LED QTY	6LEDs	6pcs RGBW 4IN1 LEDs		
Performance				
Lumen Output	1260lm	900lm		
Efficacy	70lm/W based at W3000K	50lm/W based at W3000K		
Beam Angle	15° 25° 40° 60°	25° 40° 60°		
Electrical				
Input Voltage	120-277VAC	24VDC		
Power Consumption	18W	18W		
Control				
Protocols	Light On-off	DMX		
Addressing	N/A	Manual addresing with CD Smart addresse		
Physical				
Housing	6063 high density extruded	aluminium alloy		
Lens	4mm Tempered Glass			
Finish	Powder coating, Black/White/Grey or Custom RAL Color			
Dimensions (L X W X H)	60x100x152mm			
Cable Entry	Bottom Entry			
Mounting	Surface Mounting			






-31-



Dimension & Accessories



LED Inground Light-GL50


Static White/RGBW

The Nowox Led GL80 LED Inground is a IP66 rated exterior inground light with high output brightness.

Product Specification

Models LED	GL500101	GL500104
Color	Static W hite	RGBW tot General Bacar White.
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:618-628nm G:525-535nm B:465-475nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	1ED	1pcs RGBW 4IN1 LED
Performance		
Lumen Output	384lm	250lm
Efficacy	70lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	10° 20° 30° 45° 15°X40°	20° 30° 45° 60°
Electrical		
Input Voltage	24VDC	24VDC
Power Consumption	4.5W	4.5W
Control		
Protocols	Light on off / DMX	DMX
Addressing	Manual Addressing with Nowox Led Addr	essing Tool
Physical		
Housing	Stainless steel with Tempered Glass	
Lens	4mm Tempered Glass	
Finish	Silver Anodised	
Dimensions (L X W X H)	Diameter 50X75mm	
Cable Entry	Bottom Entry	
Mounting	Recessed Mounting	


Archiectural Lighting -32-







Dimension & Accessories





LED Inground Light-GL80

Static White/RGBW


The Nowox Led GL80 LED Inground is a IP66 rated exterior inground light with high output brightness.

Models LED	GL800101	GL800104
Color	Static W hite	RGBW tod Comes Black White
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:618-628nm G:525-535nm B:465-475nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	1ED	1pcs RGBW 4IN1 LED
Performance		
Lumen Output	768lm	500lm
Efficacy	70lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	10° 20° 30° 45° 15°X40°	20° 30° 45° 60°
Electrical		
Input Voltage	24VDC	24VDC
Power Consumption	10W	10W
Control		
Protocols	Light on off / DMX	DMX
Addressing	Manual Addressing with Nowox Led Addr	essing Tool
Physical		
Housing	Stainless steel with Tempered Glass	
Lens	4mm Tempered Glass	
Finish	Silver Anodised	
Dimensions (L X W X H)	Diameter 50X75mm	
Cable Entry	Bottom Entry	
Mounting	Recessed Mounting	





System Diagram



LED Flood Light – Q105

Static White/RGBW

The Nowox Led Q105 is a DC Version exterior luminaire to light the landmarks facades,walls, andwith powerful color washer effects.

This floodlight is available in RGBW (3000K or 4000K), Warm White (3000K), Neutral White (4000K) or Cold White (5700K).

Models LED	Q1050801	Q1050804
Color	Static W hite	RGBW that Graves that White
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	8LEDs	8pcs RGBW 4IN1 LEDs
Performance		
Lumen Output	1440lumenlumen	900lumen
Efficacy	80lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	8° 12° 20° 30° 45°	17° 25° 45° 60°
Electrical		
Input Voltage	24VDC	24VDC
Power Consumption	18W	18W
Control		
Protocols	Light On/Off or DMX	DMX
Addressing	Manual Addressing with Nowox Led Addre	essing Tool
Pixels	1Pixel	1Pixel
Physical		
Material	Aluminum 6063 with Tempered Glass	
Finish Color	Powder coating Deep Grey	
Cable Entry	Bottom Entry	
Dimensions (L X W X H)	105X107X148mm	


Surface Mounting

Half Glare Shield


Mounting

Accessory





System Diagram



LED Flood Light – Q130

Static White/RGBW

The Nowox Led Q130 is a DC Version exterior luminaire to light the landmarks facades,walls, andwith powerful color washer effects.


This floodlight is available in RGBW (3000K or 4000K), Warm White (3000K), Neutral White (4000K) or Cold White (5700K).

Models LED	Q1301201	Q1301204
Color	Static W hite	RGBW fad Green Blay Wilde
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	12LEDs	12pcs RGBW 4IN1 LEDs
Performance		
Lumen Output	1920lumen	1200lumen
Efficacy	80lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	8° 12° 20° 30° 45°	17° 25° 45° 60°
Electrical		
Input Voltage	24VDC	24VDC
Power Consumption	24W	24W
Control		
Protocols	Light On/Off or DMX	DMX
Addressing	Manual Addressing with Nowox Led Addre	ssing Tool
Pixels	1Pixel	1Pixel
Physical		
Material	Aluminum 6063 with Tempered Glass	
Finish Color	Powder coating Deep Grey	
Cable Entry	Bottom Entry	
Dimensions (L X W X H)	130x107x178mm	
Mounting	Surface Mounting	
Accessory	Half Glare Shield	





System Diagram



LED Flood Light – Q160

Static White/RGBW

The Nowox Led Q160 is a DC Version exterior luminaire to light the landmarks facades,walls, andwith powerful color washer effects.


This floodlight is available in RGBW (3000K or 4000K), Warm White (3000K), Neutral White (4000K) or Cold White (5700K).

Models LED	Q1601601	Q1601604
Color	Static W hite	RGBW Red Great Rest White
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	16LEDs	16pcs RGBW 4IN1 LEDs
Performance		
Lumen Output	2880lumen	1800lumen
Efficacy	80lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	8° 12° 20° 30° 45°	17° 25° 45° 60°
Electrical		
Input Voltage	120-277VAC	120-277VAC
Power Consumption	36W	36W
Control		
Protocols	Light On/Off or DMX	DMX
Addressing	Manual Addressing with Nowox Led Addre	ssing Tool
Pixels	1Pixel	1Pixel
Physical		
Material	Aluminum 6063 with Tempered Glass	
Finish Color	Powder coating Deep Grey	
Cable Entry	Bottom Entry	
Dimensions (L X W X H)	160x107x218mm	
Mounting	Surface Mounting	
Accessory	Half Glare Shield	





System Diagram



LED Flood Light - Q185

Static White/RGBW

Finish Color

Cable Entry

Dimensions

(LXWXH)

Mounting

Accessory

The Nowox Led Q185 is a DC Version exterior luminaire to light the landmarks facades, walls, and with powerful color washer effects.

This floodlight is available in RGBW (3000K or 4000K), Warm White (3000K), Neutral White (4000K)

Models LED	Q1852401	Q1852404
Color	Static W hite	RGBW And Crease Black Wilder
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	24LEDs	24pcs RGBW 4IN1 LEDs
Performance		
Lumen Output	3840lumen	2400lumen
Efficacy	80lm/W based at W3000K	50lm/W based at W3000K
Beam Angle		
	8° 12° 20° 30° 45	17° 25° 45° 60°
Electrical		
Input Voltage	120-277VAC	120-277VAC
Power Consumption	48W	48W
Control		
Protocols	Light On/Off or DMX	DMX
Addressing	Manual Addressing with Nowox I	ed Addressing Tool
Pixels	1Pixel	1Pixel
Physical		
Material	Aluminum 6063 with Tempered Gla	ass

Powder coating Deep Grey

Bottom Entry

185x120x247mm

Surface Mounting


Half Glare Shield

Archiectural Lighting





System Diagram




LED Flood Light - Q220


Static White/RGBW

The Nowox Led Q220 is a DC Version exterior luminaire to light the landmarks facades, walls, and with powerful color washer effects.


This floodlight is available in RGBW (3000K or 4000K), Warm White (3000K), Neutral White (4000K) or Cold White (5700K).

Models LED	Q2204801	Q2204804
Color	Static White	RGBW Red Green Blace White
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	48LEDs	48pcs RGBW 4IN1 LEDs
Performance		
Lumen Output	7680lumen	4800lumen
Efficacy	80lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	8° 12° 20° 30° 45°	17° 25° 45° 60°
Electrical		
Input Voltage	120-277VAC	120-277VAC
Power Consumption	96W	96W
Control		
Protocols	Light On/Off or DMX	DMX
Addressing	Manual Addressing with Nowox Led Addre	essing Tool
Pixels	1Pixel	1Pixel
Physical		
Material	Aluminum 6063 with Tempered Glass	
Finish Color	Powder coating Deep Grey	
Cable Entry	Bottom Entry	
Dimensions (L X W X H)	220X175X307mm	
Mounting	Surface Mounting	





System Diagram




LED Flood Light - F110

Static White/RGBW

This LED Flood Light is designed for architectural Facade, bridge and so on. It can deliver high efficiency light output and uniform beam with professional lens. We used Top Brand Silicone for better heat conduction, strong temperature withstands and perfect waterproof performance.

Models LED	F1100601	F1100604
Color	Static W hite	RGBW Red Green Black White
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	6LEDs	6pcs RGBW 4IN1 LEDs
Performance		
Lumen Output	1200lumen	900lumen
Efficacy	80lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	8° 12° 20° 30° 45°	17° 25° 45° 60°
Electrical		
Input Voltage	24VDC	24VDC
Power Consumption	15W	15W
Control		
Protocols	Light On/Off or DMX	DMX
Addressing	Manual Addressing with Nowox Led Addres	ssing Tool
Pixels	1Pixel	1Pixel
Physical		
Material	Aluminum 6063 with Tempered Glass	
Finish Color	Powder coating Deep Grey	
Cable Entry	Bottom Entry	
Dimensions (L X W X H)	124X148X151mm	
Mounting	Surface Mounting	
Accessory	Half Glare Shield	



Dimension System Diagram

-47-

LED Flood Light - F130

Static White/RGBW


This LED Flood Light is designed for architectural Facade, bridge and so on. It can deliver high efficiency light output and uniform beam with professional lens. We used Top Brand Silicone for better heat conduction, strong temperature with stands and perfect waterproof performance.

Product Specification

Models LED	F1301201	F1301204
Color	Static W hite	RGBW Int Green Black White
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	12LEDs	12pcs RGBW 4IN1 LEDs
Performance		
Lumen Output	1900lumen	1200lumen
Efficacy	80lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	8° 12° 20° 30° 45°	17° 25° 45° 60°
Electrical		
Input Voltage	24VDC	24VDC
Power Consumption	24W	24W
Control		
Protocols	Light On/Off or DMX	DMX
Addressing	Manual Addressing with Nowox Led Addre	ssing Tool
Pixels	1Pixel	1Pixel
Physical		
Material	Aluminum 6063 with Tempered Glass	
Finish Color	Powder coating Deep Grey	
Cable Entry	Bottom Entry	
Dimensions (L X W X H)	144X181X172mm	
Mounting	Surface Mounting	
Accessory	Half Glare Shield	


-48-

Archiectural Lighting



Dimension 247 247 213 Sustan Discussion

System Diagram



LED Flood Light - F160

Static White/RGBW

This LED Flood Light is designed for architectural Facade, bridge and so on.It can deliver high efficiency light output and uniform beam with professional lens. We used Top Brand Silicone for better heat conduction, strong temperature withstands and perfect waterproof performance.

Models LED	F1601801	F1601804
Color	Static W hite	RGBW
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	18LEDs	18pcs RGBW 4IN1 LEDs
Performance		
Lumen Output	2880lumen	1800lumen
Efficacy	80lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	8° 12° 20° 30° 45°	17° 25° 45° 60°
Electrical		
Input Voltage	120-277VAC	120-277VAC
Power Consumption	36W	36W
Control		
Protocols	Light On/Off or DMX	DMX
Addressing	Manual Addressing with Nowox Led Addre	essing Tool
Pixels	1Pixel	1Pixel
Physical		
Material	Aluminum 6063 with Tempered Glass	
Finish Color	Powder coating Deep Grey	
Cable Entry	Bottom Entry	
Dimensions (L X W X H)	182X247X213mm	
Mounting	Surface Mounting	
Accessory	Half Glare Shield	



Dimension System Diagram

IP66 Junction Box (by others)

-51-

LED Flood Light – F180

Static White/RGBW

This LED Flood Light is designed for architectural Facade, bridge and so on.It can deliver high efficiency light output and uniform beam with professional lens. We used Top Brand Silicone for better heat conduction, strong temperature withstands and perfect waterproof performance.

Models LED	F1802401	F1802404
Color	Static W hite	RGBW And Green Base White
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	24LEDs	24pcs RGBW 4IN1 LEDs
Performance		
Lumen Output	3840lumen	2400lumen
Efficacy	80lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	8° 12° 20° 30° 45°	17° 25° 45° 60°
Electrical		
Input Voltage	120-277VAC	120-277VAC
Power Consumption	48W	48W
Control		
Protocols	Light On/Off or DMX	DMX
Addressing	Manual Addressing with Nowox Led Addre	ssing Tool
Pixels	1Pixel	1Pixel
Physical		
Material	Aluminum 6063 with Tempered Glass	
Finish Color	Powder coating Deep Grey	
Cable Entry	Bottom Entry	
Dimensions (L X W X H)	203X260X242mm	
Mounting	Surface Mounting	
Accessory	Half Glare Shield	



Dimension | System Diagram | Date |

IP66 Junction Box (by others)

-53-

LED Flood Light - F210


Static White/RGBW

This LED Flood Light is designed for architectural Facade, bridge and so on. It can deliver high efficiency light output and uniform beam with professional lens. We used Top Brand Silicone for better heat conduction, strong temperature withstands and perfect waterproof performance.

Color Issaer Resw Light Source High Power LED High Power LED Color 2700K 3000K 4000K 4000K 5700K 81450-4655mm B14450-4655mm W:3000K/4000K/6500K R:620-630nm G:520-535nm B1450-4655mm W:3000K/4000K/6500K CRI for White LED Ra>80 Ra>80 LED QTY 36LEDs 36pcs RGBW 4IN1 LEDs Performance Lumen Output 5760lumen 3600lumen Efficacy 80lm/W based at W3000K 50lm/W based at W3000K Beam Angle 8° 12° 20° 30° 45° 17° 25° 45° 60° Electrical Input Voltage 120-277VAC 120-277VAC Power Consumption 72W 72W Control Protocols Light On/Off or DMX DMX Addressing Manual Addressing with Nowox Led Addressing Tool Pixels 1Pixel 1Pixel Physical Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (LX W X H) 233X313X273mm	Models LED	F2103601	F2103604
Color 2700K 3000K 4000K 5700K 6500K R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/6500K CRI for White LED Ra>80 Ra>80 LED QTY 36LEDs 36pcs RGBW 4IN1 LEDs Performance Lumen Output 5760lumen 3600lumen Efficacy 80lm/W based at W3000K 50lm/W based at W3000K Beam Angle 80lm/W based at W3000K 50lm/W based at W3000K Electrical Input Voltage 120-277VAC 120-277VAC Power Consumption 72W 72W Control Protocols Light On/Off or DMX DMX Addressing Manual Addressing with Nowox Led Addressing Tool Pixels 1Pixel Physical Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (LX W X H) 333X313X273mm Mounting Surface Mounting	Color		RGBW Intel Green Dian White
Section	Light Source	High Power LED	High Power LED
LED QTY 36LEDS 36pcs RGBW 4IN1 LEDS	Color	3000K 4000K 5700K	G:520-535nm B:450-465nm
Lumen Output 5760lumen 3600lumen Efficacy 80lm/W based at W3000K 50lm/W based at W3000K Beam Angle Electrical Input Voltage 120-277VAC 120-277VAC Power Consumption 72W 72W Control Protocols Light On/Off or DMX DMX Addressing Manual Addressing with Nowox Led Addressing Tool Pixels 1Pixel 1Pixel Physical Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) Sollow Boolumen 3600lumen 360	CRI for White LED	Ra>80	Ra>80
Electrical Input Voltage 120-277VAC 120-277VAC Power Consumption 72W 72W Control Protocols Light On/Off or DMX DMX Addressing Manual Addressing with Nowox Led Addressing Tool Pixels 1Pixel 1Pixel Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) Mounting Surface Mounting Sollm/W based at W3000K 50lm/W based at W3000K 60' 45° 60° Fixel 120-277VAC 72W Fixel 120-277VAC 120-27	LED QTY	36LEDs	36pcs RGBW 4IN1 LEDs
Efficacy 80lm/W based at W3000K 50lm/W based at W3000K Beam Angle Electrical Input Voltage 120-277VAC 120-277VAC Power Consumption 72W 72W Control Protocols Light On/Off or DMX DMX Addressing Manual Addressing with Nowox Led Addressing Tool Pixels 1Pixel 1Pixel Physical Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) Mounting Surface Mounting	Performance		
Beam Angle Beam Angle	Lumen Output	5760lumen	3600lumen
Electrical Input Voltage 120-277VAC 120-277VAC Power Consumption 72W 72W Control Protocols Light On/Off or DMX DMX Addressing Manual Addressing with Nowox Led Addressing Tool Pixels 1Pixel 1Pixel Physical Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) Mounting Surface Mounting	Efficacy	80lm/W based at W3000K	50lm/W based at W3000K
Input Voltage 120-277VAC 120-277VAC Power Consumption 72W 72W Control Protocols Light On/Off or DMX DMX Addressing Manual Addressing with Nowox Led Addressing Tool Pixels 1Pixel 1Pixel Physical Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) Mounting Surface Mounting	·	8° 12° 20° 30° 45°	17° 25° 45° 60°
Input Voltage 120-277VAC 120-277VAC Power Consumption 72W 72W Control Protocols Light On/Off or DMX DMX Addressing Manual Addressing with Nowox Led Addressing Tool Pixels 1Pixel 1Pixel Physical Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) 233X313X273mm Mounting Surface Mounting	Electrical		
Control Protocols Light On/Off or DMX DMX Addressing Manual Addressing with Nowox Led Addressing Tool Pixels 1Pixel 1Pixel Physical Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) 233X313X273mm Mounting Surface Mounting	Input Voltage	120-277VAC	120-277VAC
Protocols Light On/Off or DMX Addressing Manual Addressing with Nowox Led Addressing Tool Pixels 1Pixel Physical Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) Surface Mounting DMX DMX DMX DMX DMX DMX Dimensiong Tool 1Pixel	Power Consumption	72W	72W
Addressing Manual Addressing with Nowox Led Addressing Tool Pixels 1Pixel 1Pixel Physical Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) 233X313X273mm Mounting Surface Mounting	Control		
Physical Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) 233X313X273mm Mounting Surface Mounting	Protocols	Light On/Off or DMX	DMX
Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) 233X313X273mm Mounting Surface Mounting	Addressing	Manual Addressing with Nowox Led Addre	essing Tool
Material Aluminum 6063 with Tempered Glass Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) 233X313X273mm Mounting Surface Mounting	Pixels	1Pixel	1Pixel
Finish Color Powder coating Deep Grey Cable Entry Bottom Entry Dimensions (L X W X H) 233X313X273mm Mounting Surface Mounting	Physical		
Cable Entry Dimensions (L X W X H) Surface Mounting Bottom Entry 233X313X273mm Surface Mounting	Material	Aluminum 6063 with Tempered Glass	
Dimensions (L X W X H) Mounting Surface Mounting	Finish Color	Powder coating Deep Grey	
(L X W X H) 233X313X273mm Mounting Surface Mounting	Cable Entry	Bottom Entry	
		233X313X273mm	
Accessory Half Glare Shield	Mounting	Surface Mounting	
	Accessory	Half Glare Shield	



Dimension 230 230 System Diagram





LED Flood Light - F260

Static White/RGBW


This LED Flood Light is designed for architectural Facade, bridge and so on. It can deliver high efficiency light output and uniform beam with professional lens. We used Top Brand Silicone for better heat conduction, strong temperature withstands and perfect waterproof performance.

Models LED	F2604801	F2604804
Color	Static W hite	RGBW Red Green Day Wilde
Light Source	High Power LED	High Power LED
Color	2700K 3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/6500K
CRI for White LED	Ra>80	Ra>80
LED QTY	48LEDs	48pcs RGBW 4IN1 LEDs
Performance		
Lumen Output	9600lumen	6000lumen
Efficacy	80lm/W based at W3000K	50lm/W based at W3000K
Beam Angle	8° 12° 20° 30° 45°	17° 25° 45° 60°
Electrical		
Input Voltage	120-277VAC	120-277VAC
Power Consumption	120W	120W
Control		
Protocols	Light On/Off or DMX	DMX
Addressing	Manual Addressing with Nowox Led Addre	essing Tool
Pixels	1Pixel	1Pixel
Physical		
Material	Aluminum 6063 with Tempered Glass	
Finish Color	Powder coating Deep Grey	
Cable Entry	Bottom Entry	
Dimensions (L X W X H)	260X230X331mm	
Mounting	Surface Mounting	
Accessory	Half Glare Shield	





System Diagram



LED Flood Light - F490

Static White/RGBW


This LED Flood Light is designed for architectural Facade, bridge and so on. It can deliver high efficiency light output and uniform beam with professional lens. We used Top Brand Silicone for better heat conduction, strong temperature withstands and perfect waterproof performance.


Product Specification

Models LED	F4907201	F4907204	F4909604
Color	Static W hite	RGBW fed Green Black White	RGBW tad Green Blau White
Light Source	High Power LED	High Power LED	High Power LED
Color	3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/ 5700K/6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/ 5700K/6500K
CRI for White LED	Ra>80	Ra>80	Ra>80
LED QTY	72LEDs	72LEDs RGBW 4IN1	96LEDs(Discrete) 24R+24G+24B+24W
Performance			
Lumen Output	12800lumen	11600lumen	
Efficacy	80lumen /W	58lumen /W	58lumen /W
Beam Angle			
8° Electrical	12° 20° 30° 4	5° 17° 25° 45° 60	° 8° 12° 20° 30° 45°
Input Voltage	120-277VAC	120-277VAC	120-277VAC
Power Consumption	150W	150W	150W
Control			
Protocols	Light On/Off or DMX-	-RDM DMX/RDM	DMX/RDM
Addressing	Manual Addressing	with Nowox Led Address	ing Tool
Pixels	1Pixel	1Pixel	1Pixel
Physical			
Housing	Die cast aluminum		
Cover lens	Tempered glass		
Housing Finish	Deep Gray or Black		
Dimensions (L X W X H)	490X173X308mm		
Cable Entry	Bottom entry		
Mounting	Surface Mounting		
Accessory	Glare shield		

-58-

Archiectural Lighting -57-








System Diagram

- 59-



LED Flood Light - F490D

Static White/RGBW


This LED Flood Light is designed for architectural Facade, bridge and so on. It can deliver high efficiency light output and uniform beam with professional lens. We used Top Brand Silicone for better heat conduction, strong temperature withstands and perfect waterproof performance.


Product Specification


Models LED	F4907201D	F4907204D	F4909604D
Color	Static W hite	RGBW Red Green Blau White	RGBW had Green Blue White
Light Source	High Power LED	High Power LED	High Power LED
Color	3000K 4000K 5700K 6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/ 5700K/6500K	R:620-630nm G:520-535nm B:450-465nm W:3000K/4000K/ 5700K/6500K
CRI for White LED	Ra>80	Ra>80	Ra>80
LED QTY	2 X 72LEDs	2 X 72LEDs RGBW 4IN1	2 X 96LEDs(Discrete) 24R+24G+24B+24W
Performance			
Lumen Output	2 X 12800lumen	2 X 11600lumen	
Efficacy	80lumen /W	58lumen /W	58lumen /W
Beam Angle	1		:
8°	12° 20° 30° 45°	17° 25° 45° 60°	8° 12° 20° 30° 45
Electrical			
Electrical Input Voltage	120-277VAC	120-277VAC	120-277VAC
Electrical Input Voltage Power Consumption			
Electrical Input Voltage Power Consumption Control	120-277VAC 300W	120-277VAC 300W	120-277VAC 300W
Electrical Input Voltage Power Consumption Control Protocols	120-277VAC 300W Light On/Off or DMX-RDM	120-277VAC 300W DMX/RDM	120-277VAC 300W DMX/RDM
Electrical Input Voltage Power Consumption Control Protocols Addressing	120-277VAC 300W Light On/Off or DMX-RDM Manual Addressing with N	120-277VAC 300W DMX/RDM Nowox Led Addressing	120-277VAC 300W DMX/RDM Tool
Electrical Input Voltage Power Consumption Control Protocols Addressing Pixels	120-277VAC 300W Light On/Off or DMX-RDM	120-277VAC 300W DMX/RDM	120-277VAC 300W DMX/RDM
Electrical Input Voltage Power Consumption Control Protocols Addressing	120-277VAC 300W Light On/Off or DMX-RDM Manual Addressing with N	120-277VAC 300W DMX/RDM Nowox Led Addressing	120-277VAC 300W DMX/RDM Tool
Electrical Input Voltage Power Consumption Control Protocols Addressing Pixels Physical	120-277VAC 300W Light On/Off or DMX-RDM Manual Addressing with N 1Pixel	120-277VAC 300W DMX/RDM Nowox Led Addressing	120-277VAC 300W DMX/RDM Tool
Electrical Input Voltage Power Consumption Control Protocols Addressing Pixels Physical Housing	120-277VAC 300W Light On/Off or DMX-RDM Manual Addressing with N 1Pixel Die cast aluminum	120-277VAC 300W DMX/RDM Nowox Led Addressing	120-277VAC 300W DMX/RDM Tool
Electrical Input Voltage Power Consumption Control Protocols Addressing Pixels Physical Housing Cover lens	120-277VAC 300W Light On/Off or DMX-RDM Manual Addressing with N 1Pixel Die cast aluminum Tempered glass	120-277VAC 300W DMX/RDM Nowox Led Addressing	120-277VAC 300W DMX/RDM Tool
Electrical Input Voltage Power Consumption Control Protocols Addressing Pixels Physical Housing Cover lens Housing Finish Dimensions	120-277VAC 300W Light On/Off or DMX-RDM Manual Addressing with N 1Pixel Die cast aluminum Tempered glass Deep Gray or Black	120-277VAC 300W DMX/RDM Nowox Led Addressing	120-277VAC 300W DMX/RDM Tool
Electrical Input Voltage Power Consumption Control Protocols Addressing Pixels Physical Housing Cover lens Housing Finish Dimensions (L X W X H)	120-277VAC 300W Light On/Off or DMX-RDM Manual Addressing with N 1Pixel Die cast aluminum Tempered glass Deep Gray or Black 554X173X501mm	120-277VAC 300W DMX/RDM Nowox Led Addressing	120-277VAC 300W DMX/RDM Tool

-60-










System Diagram




DMX Media Tube - Glowline 18


Static White/Tunable White/RGB/RGBW

The Colordreamer DMX Media Bar is a 18mm wide exterior DMX Direct-view Linear with Clear, black, Opal PC and Opal Acrylic Diffuser. Fixtured Mounting Brackets or customized brackets are available. User can choose auto addressing for fast installation or RDM addressing for Monitoring.

Models LED	LX181006001	LX181006002	LX181006003	LX181006004
Color	Static W hite	Tunable W hite	RGB Red Green Blos	RGBW fad Green Blay White
Light Source	SMD LED	SMD LED	SMD LED	SMD LED
Color	W:3000K W:4000K W:5700K	W:3000K W:5700K	R:619-624nm G:520-540nm B:460-480nm	R:619-624nm G:520-540nm B:460-480nm W:3000K/4000K/5700K
CRI for White LED	Ra>80	Ra>80	-	Ra>80
LED QTY	60LEDs	60LEDs	60LEDs	60LEDs
Performance				
Lumen Output	Update soon	Update soon	Update soon	844lumen/Clear @CREE RGBW(W3000K) 415lumen Acrylic Top @CREE RGBW(W3000K)
Efficacy	Update soon	Update soon	Update soon	844lumen/Clear @CREE RGBW(W3000K) 415lumen Acrylic Top @CREE RGBW(W3000K)
Beam Angle	110° Cle	ar Cover / 165°	Black Cover/Opa	al Cover/Acrylic Cover
Electrical				
Input Voltage	24VDC	24VDC	24VDC	24VDC
Power Consumptio	n 10W/Meter	10W/Meter	10W/Meter	10W/Meter
Control				
Protocols	DMX512 Control	DMX512 Control	DMX512 Control	DMX512 Control
PWM Frequency	16Bit			
Addressing	Manual addressir	ng by daisy-chain		
Pixels	10Pixels/m	10Pixels/m	10Pixels/m	10Pixels/m
Physical				
Material	Aluminum 6063	with UV Protected C	Cover	
Finish Color	Powder coating, I	Black/Grey Silver or	Custom RAL Color	
Cover	Clear/PC Black/P	C Opal/Acrylic		
Dimensions (L X W X H)	1000mm*28.5m	1000mm*28.5mm*50mm(for Clear Cover) 1000mm*28.5mm*64mm(for PMMA Dome) 1000mm*28.5mm*64mm(for PC Dome)		
Length	500mm/1000mr	n/305mm/1200mm	1	







DMX Pixel Dot - Glowline 28

Static White/Tunable White/RGB/RGBW

The Nowox Led DMX Media Bar is a 28mm wide exterior DMX Direct-view Linear with Clear, black, Opal PC and Opal Acrylic Diffuser. Fixtured Mounting Brackets or customized brackets are available. User can choose auto addressing for fast installation or RDM addressing for Monitoring.

Models LED	LX281006001	LX281006002	LX281006003	LX281006004
Color	Static W hite	Tunable W hite	RGB And Green Blue	RGBW Red Green Star White
Light Source	SMD 3535 LED	SMD 3535 LED	SMD 3535 LED	SMD 3535 LED
Color	W:3000K W:4000K W:5700K	W:3000K W:5700K	R:619-624nm G:520-540nm B:460-480nm	R:619-624nm G:520-540nm B:460-480nm W:3000K/4000K/5700K
CRI for White LED	Ra>80	Ra>80	-	Ra>80
LED QTY	60LEDs	60LEDs	60LEDs	60LEDs
Performance				
Lumen Output	Update soon	Update soon	Update soon	844lumen/Clear @CREE RGBW(W3000K) 415lumen Acrylic Top @CREE RGBW(W3000K)
Efficacy	Update soon	Update soon	Update soon	844lumen/Clear @CREE RGBW(W3000K) 415lumen Acrylic Top @CREE RGBW(W3000K)
Beam Angle	110° Cle	ar Cover / 165° I	Black Cover/Op	al Cover/Acrylic Cover
Electrical				
Input Voltage	24VDC	24VDC	24VDC	24VDC
Power Consumption	n 10W/Meter	10W/Meter	10W/Meter	10W/Meter
Control				
Protocols	DMX512 Control	DMX512 Control	DMX512 Control	DMX512 Control
PWM Frequency	16Bit			
Addressing	Manual addressin	g by daisy-chain		
Pixels	10Pixels/m 20Pixels/m	10Pixels/m 20Pixels/m	10Pixels/m 20Pixels/m	10Pixels/m 20Pixels/m
Physical				
Material	Aluminum 6063	with UV Protected C	Cover	
Finish Color	Powder coating,	Black/Grey Silver or	Custom RAL Color	
Cover	Clear/PC Black/P	C Opal/Acrylic		
Dimensions (L X W X H)	1000mm*39mm	1000mm*39mm*61.7mm(for Clear Cover) 1000mm*39mm*75mm(for PMMA Dome) 1000mm*39mm*81mm(for PC Dome)		
Length	500mm/1000mr	m/305mm/1200mm	1	






















Dimension



System Diagram



Option 2





DMX Pixel Dot - DC40

Static White/RGB/RGBW

The Colordreamer DC40 LED Pixel Dot is an exterior mini size Direct-view dot with high output brightness. Clear or diffused lens available for different application. Custom pixel pitch from 100mm to 1000mm.

Models LED	DC400603	DC400604	
Color	R _{GB}	RGBW tod Green they Wilde	
Light Source	Epistar or Cree LED	Epistar or Cree LED	
Color	R:619-624nm G:520-540nm B:460-480nm	R:619-624nm G:520-540nm B:460-480nm W:3000K/4000K/5700K	
CRI for White LED	-	Ra>80	
LED QTY	6LEDs	6 RGB LEDs+2 White LEDs	
Performance			
Lumen Output	Update soon	50lumen/Transparent Flat Lens CREE RGBW(W3000K) 37lumen/Diffused Bulb Lens CREE RGBW(W3000K)	
Efficacy	Update soon	38lumen/W Transparent Flat Lens CREE RGBW(W3000K) 27lumen/W Diffused Bulb Lens CREE RGBW(W3000K)	
Beam Angle	110°Transparent Flat Lens		
Electrical			
Input Voltage	24VDC	24VDC	
Power Consumption	1.4W	1.8W	
Control			
Protocols	DMX512 Control	DMX512 Control DMX512 Control	
PWM Frequency	16Bit		
Addressing	Manual Addressing	with Nowox Led Addressing Tool CD-MT512	
Physical			
Material	Polycarbonate Body v	vith UV Protected Lens	
Finish Color	Transparent		
Optics	Transparent Flat Lens		
Dimensions (L X W X H)	47.5X40X15mm		
Cable Entry	Side Entry		
Max.length	10Meter per string		





OUTDOOR

NO.3

NO.40

DMX Terminator /End Cap

INDOOR
Leader Cable 4PIN to open wire

DMX Signal

-67-

DMX Pixel Dot - DX60

Static White/RGB/RGBW

The Colordreamer DX60 LED Pixel Dot is an exterior mini size Direct-view dot with high output brightness. Clear or diffused lens available for different application. Custom pixel pitch from 100mm to 1000mm.

Models LED	DX600601	DX600603	DX600604		
Color	Static W hite	RGB ted Green Stude	RGBW Red Clean Black Whites		
Light Source	Epistar or Cree LED	Epistar or Cree LED	Epistar or Cree LED		
Color	W:3000K W:4000K W:5700K	R:619-624nm G:520-540nm B:460-480nm	R:619-624nm G:520-540nm B:460-480nm W:3000K/4000K/5700K		
CRI for White LED	Ra>80	-	Ra>80		
LED QTY	6LEDs	6LEDs	6LEDs		
Performance					
Lumen Output	Update soon	Update soon	93lumen/Transparent Flat Lens RGBW(W3000K) 48lumen/Diffused Dome Lens RGBW(W3000K)		
Efficacy	Update soon	Update soon	38lumen/W Transparent Flat Lens / RGBW(W3000K) 18lumen/W Diffused Dome Lens / RGBW(W3000K)		
Beam Angle	100°Transparent	: Flat Lens/110° Diff	used Dome Lens		
Electrical					
Input Voltage	24VDC	24VDC	24VDC		
Power Consumption	2W	2W	2W		
Control					
Protocols	DMX512 Control	DMX512 Control	DMX512 Control		
PWM Frequency	16Bit				
Addressing	Manual addressing p	er daisy-chain			
Physical					
Material	Aluminum 6063 Bod	ly with UV Protected Cov	er		
Finish Color	Black or Custom RAL	Black or Custom RAL Color			
Optics	Transparent Flat Len	s/ Diffused Dome Lens			
Dimensions (L X W X H)		64X56.5X37.5mm (Transparent Flat Lens) 64X56.5X37.5mm (Diffused Dome Lens)			
Cable Entry	Side Entry/Bottom E	ntry			
Mounting	Surface Mounting wi	th Screw			








































System Diagram





DMX Pixel Dot - DX88

Static White/RGB/RGBW

The Colordreamer DX88 LED Pixel Dot is an exterior middle size Direct view dot with high output brightness. High quality LEDs achieve good reliably for outdoor application. Custom pixel pitch from 100mm to 1000mm.

Models LED	DX881801	DX881803	DX881804
Color	Static W hite	RGB tod Green Blas	RGBW Red Green Blast White
Light Source	Epistar	Epistar	Epistar
Color	W:3000K W:4000K W:5700K	R:619-624nm G:520-540nm B:460-480nm	R:619-624nm G:520-540nm B:460-480nm W:3000K/4000K/5700K
CRI for White LED	Ra>80	-	Ra>80
LED QTY	18LEDs	18LEDs	18LEDs
Performance			
Lumen Output	Update soon	Update soon	184lumen/Transparent Flat Lens RGBW(W3000K) 88lumen/Diffused Dome Lens RGBW(W3000K)
Efficacy	Update soon	Update soon	46lumen/W Transparent Flatens / RGBW(W3000K) 22lumen/W Diffused Dome Lens / RGBW(W3000K)
Beam Angle	100°Transparent Flat Lens/140° Diffused Dome Lens		
Electrical			
Input Voltage	24VDC	24VDC	24VDC
Power Consumption	4W	4W	4W
Control			
Protocols	DMX512 Control	DMX512 Control	DMX512 Control
PWM Frequency	16Bit		
Addressing	Manual addressing p	er daisy-chain or RDM a	addressing
Physical			
Material	Aluminum 6063 Boo	ly with UV Protected Co	ver
Finish Color	Powder coating, Blac	ck/Grey Silver or Custon	n RAL Color
Optics	Transparent Flat Ler	ns/ Diffused Dome Lens	
Dimensions (L X W X H)	98X73X50mm (Transparent Flat Lens) 98X73X65mm (Diffused Dome Lens)		
Cable Entry	Side Entry/Bottom E	intry	
Mounting	Surface Mounted		

24V UV 16W DMXDC resistant Warranty **3 (E** RoHS IP20 **Dimension System Diagram** Option 1 INDOOR OUTDOOR Leader Cable 2PIN for Power Jumper Cable DMX IN □ IP67 Connector to XLR 5PIN Cable Option 2 OUTDOOR **INDOOR** -71- DMX IN □ DMX Signal

Direct DMX Pixel Strip - DS126004

Static White/Tunable White/RGB/RGBW

The Nowox Led DMX Flex Strip are flexible strips which can be controlled directly using DMX512. The strip provides flexibility to fit on any curved surface.

We have used superior thickened 30Z copper tracks to reduce the effects of voltage drop.

Models LED	DS126001	DS126002	DS126003	DS126004
Color	Static W hite	Tunable W hite	RGB Nat Green Blue	RGBW Red Green Star Wikha
Light Source	SMD 5050	SMD 5050	SMD 5050	SMD 5050
	W:2700K W:3000K W:4000K W:6500K	W:3000K W:5700K	RGB	RGBW W:2700K W:3000K W:4000K W:6500K
CRI for White LED	Ra>80	Ra>80	-	Ra>80
LED QTY	60LEDs per met	er		
LED Spacing	16.6mm			
Performance				
Lumen Output	530lm	830lm	480lm	750lm
Efficacy	44lm/W	46lm/W	-	-
Beam Angle	120°			
Electrical				
Input Voltage	24VDC	24VDC	24VDC	24VDC
Power Consumptio	n 12W/Meter	12W/Meter	12W/Meter	16W/Meter
Control				
Protocols	DMX512			
Addressing	Manual Address	sing with Nowox Le	ed Addressing Too	ol CD-MT512
Pixels	10pixels/m			
LEDs per Pixel	6			
Pixel Pitch	100mm			
Cutting Pitch	100mm			
Physical				
Material	Copper 30Z			
Housing Color	Black or White			
Dimensions (W X H)	12mmX2mm			
Length	5000mm			
Mounting	3M VHB Tape for Silicone Clips for			

12V UV 12W Power DMX DC resistant Warranty ((IP20 3 -30°C to +50°C years **Dimension System Diagram** Option 1 INDOOR OUTDOOR Leader Cable 2PIN for Power Jumper Cable DMX Terminato DMX IN 🗁 IP67 Connector to XLR 5PIN Cable

OUTDOOR

Option 2

INDOOR

DMX IN 🗀

DMX Signal

Direct DMX Pixel Strip - DS124804

Static White/Tunable White/RGB/RGBW

The Nowox Led DMX Flex Strip are flexible strips which can be controlled directly using DMX512. The strip provides flexibility to fit on any curved surface.

We have used superior thickened 30Z copper tracks to reduce the effects of voltage drop.

Models LED	DS124801	DS124802	DS124803	DS124804
Color	Static W hite	Tunable W hite	RGB And Green Stee	RGBW
Light Source	SMD 5050	SMD 5050	SMD 5050	SMD 5050
Color	W:2700K W:3000K W:4000K W:6500K	W:3000K W:6500K	RGB	RGBW W:2700K W:3000K W:4000K W:6500K
CRI for White LED	Ra>80	Ra>80	-	Ra>80
LED QTY	48LEDs per met	er		
LED Spacing	20.83mm			
Performance				
Lumen Output	530lm	830lm	480lm	750lm
Efficacy	44lm/W	46lm/W	-	-
Beam Angle	120°			
Electrical				
Input Voltage	12VDC	12VDC	12VDC	12VDC
Power Consumption	n 10W/Meter	10W/Meter	10W/Meter	12W/Meter
Control				
Protocols	DMX512			
Addressing	Manual Addres	sing with Nowox	Led Addressing To	ol CD-MT512
Pixels	16pixels/m			
LEDs per Pixel	3			
Pixel Pitch	62.5mm			
Cutting Pitch	62.5mm			
Physical				
Material	Copper 3OZ			
Housing Color	Black or White			
Dimensions (W X H)	12mmX2mm			
Length	5000mm			
Mounting	3M VHB Tape for Silicone Clips for			

























System Diagram

DMX IN 🗁

DMX Šignal

Option 1



LED Strip 5050 - CC126004

RGBW

Constant current drive ensures constant current, avoids brightness changes caused by voltage fluctuations and maintains consistent brightness. Supports dimming, color adjustment and other functions, making it easy to achieve complex lighting effects.

Models LED	CC126004
Color	RGBW tat Grant But With
Light Source	SMD 5050
Color	RGBW (W:2700K W:3000K W:4000K W:6500K)
CRI for White LED	CRI>80
LED QTY	60LEDs per meter
LED Spacing	16.6mm
Performance	
Lumen Output	750lm
Efficacy	47lm per watt
Beam Angle	120°
Electrical	
Input Voltage	24VDC
Power Consumption	16W/Meter
Control	
Protocols	Contant Current Drive
Addressing	N/A
Pixels	N/A
Cutting Pitch	N/A
Physical	
Material	Copper 3OZ
Housing Color	White
Dimensions (W X H)	12mmX2mm
Length	5000mm
Mounting	3M VHB Tape for IP20 Silicone Clips for Ip67


















Dimension

-77-





LED Strip 2835 - CC1012001

Static White

Constant current drive ensures constant current, avoids brightness changes caused by voltage fluctuations and maintains consistent brightness. Supports dimming, color adjustment and other functions, making it easy to achieve complex lighting effects.

Product Specification

Models LED	CC1012001
Color	Static W hite
Light Source	SMD 2835
Color	W:2200K W:2700K W:3000K W:4000K W:6500K
CRI for White LED	CRI>90
LED QTY	120LEDs per meter
LED Spacing	8.33mm
Performance	
Lumen Output	1200lm
Efficacy	100lm per watt
Beam Angle	120°
Electrical	
Input Voltage	24VDC
Power Consumption	12W/Meter
Control	
Protocols	Contant Current Drive
Addressing	N/A
Pixels	N/A
Cutting Pitch	50mm
Physical	
Material	Copper 3OZ
Housing Color	White
Dimensions (W X H)	10mmX2mm
Length	5000mm
Mounting	3M VHB Tape for IP20 Silicone Clips for Ip67


Archiectural Lighting -78-

















Dimension







INDOOR OUTDOOR Leader Cable 2PIN for Power Power Injector Y Cable INDOOR INDOOR OUTDOOR INDOOR OUTDOOR AC IN Power Supply Junction Box DMX IN DMX IN DMX Signal

DMX Pixel Neon - DN126004

Static White/Tunable White/RGB/RGBW

The Nowox Led DMX Flex Neon are flexible strips which can be controlled directly using DMX512. The strip provides flexibility to fit on any curved surface.

We have used superior thickened 3OZ copper tracks to reduce the effects of voltage drop.

Models LED	DN128401	DN128402	DN128403	Dn128404
Color	Static W hite	Tunable W hite	RGB to d Green Blos	RGBW And Green they White
Light Source	SMD 5050	SMD 5050	SMD 5050	SMD 5050
Color	W:2700K W:3000K W:4000K W:6500K	W:2700K to W::6500K	RGB	RGBW W:2700K W:3000K W:4000K W:6500K
CRI for White LED	Ra>80	Ra>80	-	Ra>80
LED QTY	84LEDs per me	ter		
LED Spacing	11.9mm			
Performance				
Lumen Output	530lm	830lm	480lm	750lm
Efficacy	44lm/W	46lm/W	-	-
Beam Angle	120°			
Electrical				
Input Voltage	24VDC	24VDC	24VDC	24VDC
Power Consumption	on 16W/Meter	16W/Meter	16W/Meter	16W/Meter
Control				
Protocols	DMX512			
Addressing	Manual Addres	ssing with Nowox	Led Addressing To	ol CD-MT512
Pixels	12pixels/m			
LEDs per Pixel	7			
Pixel Pitch	83.33mm			
Cutting Pitch	83.33mm			
Physical				
Material	Copper 30Z			
Housing Color	White			
Dimensions (W X H)	12mmX21mm			
Length	5000mm			
Mounting	Aluminium Bra	ckets		















Warranty

years

Dimension







INDOOR OUTDOOR AC IN Power Supply Jumper Cable INDOOR OUTDOOR INDOOR OUTDOOR OUTDOOR AC IN Power Supply Jumper Cable INDOOR OUTDOOR AC IN DOWN Supply Junction Box DMX IN DMX Signal

DMX Pixel Neon - DN166004

Static White/Tunable White/RGB/RGBW

The Nowox Led DMX Flex Neon are flexible strips which can be controlled directly using DMX512. The strip provides flexibility to fit on any curved surface.

We have used superior thickened 30Z copper tracks to reduce the effects of voltage drop.

Models LED	DN168401	DN168402	DN168403	Dn168404
Color	Static W hite	Tunable W hite	RGB And Green Store	RGBW for Grow Blue White
Light Source	SMD 5050	SMD 5050	SMD 5050	SMD 5050
Color	W:2700K W:3000K W:4000K W:6500K	W:2700K to W::6500K	RGB	RGBW W:2700K W:3000K W:4000K W:6500K
CRI for White LED	Ra>80	Ra>80	-	Ra>80
LED QTY	84LEDs per me	ter		
LED Spacing	11.9mm			
Performance				
Lumen Output	530lm	830lm	480lm	750lm
Efficacy	44lm/W	46lm/W	-	-
Beam Angle	120°			
Electrical				
Input Voltage	24VDC	24VDC	24VDC	24VDC
Power Consumption	on 16W/Meter	16W/Meter	16W/Meter	16W/Meter
Control				
Protocols	DMX512			
Addressing	Manual Addres	ssing with Nowox	Led Addressing To	ol CD-MT512
Pixels	12pixels/m			
LEDs per Pixel	7			
Pixel Pitch	83.33mm			
Cutting Pitch	83.33mm			
Physical				
Material	Copper 30Z			
Housing Color	White			
Dimensions (W X H)	16mmX17mm			
Length	5000mm			
Mounting	Aluminium Bra	ckets		






Art-Net/Streaming ACN


Art-Net or Streaming ACN data is directly converted to DMX512



1DMX-IN+8DMX/RDM-Out


8 Physical outputs





Dimension

-83-



- 1. OED Screen to display the configuration menu
- 2. Control Keys

The Center ENTER button is used to confirm your operation. Short press the ENTER button to enter the next menu, long press the ENTER button to return to the previous menu. The UP/DOWN/LEFT and RIGHT keys

- 3. DMX IN
- 4. SD Card
- Status LEDs
- 6. Ethernet in and thru port
- 7. DMX1-8

ARTNET / SACN to DMX-RDM Controller

Titan A8

Art-Net/Streaming ACN

Art-Net or Streaming ACN data is directly converted to DMX512

1DMX-IN+8DMX/RDM-Out

8 Physical outputs

RDM

Each output support RDM

Ethernet in and Thru for Daisy Chain

Live Recording

Record any Art-Net or Streaming ACN network stream onto the inserted memory card.

OLED Screen or Web Configuration

Use OLED Screen or the built-in web configuration page to change specific device settings, such as the important IP address, universes, playlist settings, and much more.

Master-Slave Synchronization

Manage large projects simply by connecting several units.

Models	TITAN A8
Electrical	
Input Voltage	120-240VAC 50/60Hz C14 inlet
Power Consumption	5W
Control	
Network Protocols	Art-Net / Streaming ACN
DMX Outputs	8 Outputs (Each output 512DMX Channels)
DMX In	1X512 DMX Channels input
Ethernet	Rj45
Default IP	192.168.1.100
Default Subnet	255.255.255.0
Physical	
Material	Metal
Finish Color	Black
Connector	3pin/5pin xlr female
Dimensions (L X W X H)	483×125x45mm (Brackets)

DMX Addressing

Tool-CD-MT512

The CD-MT512 is a powerful DMX Addressing and test tool.it allows for DMX Addressing and Color testing of Lighting products. This Tool is a must for anyone involved with DMX512 installation.
























Dimension



Product Specification

Models	CD-MT512
Electrical	
Input Voltage	12-48VDC
USB Port	USB Type C, cable not included
Power Consumption	2W
Display	3.5-inch (diagonal) all-screen LCD Multi-Touch display
Control	
DMX Outputs	512 DMX Channels
Physical	
Material	Aluminium
Finish Color	Black
Connector	Removable Multi-pin terminal blocks
Dimensions (L X W X H)	114X71.2X24.8mm

Home Screen



1. IC Type can be CD/SM16512/SM175 12/SM18512/UCS-C

2.Address offset autoincrement: 0001 for one channel fixtures 0002 for 2channels fixtures 0003 for RGB fixtures 0004 for RGBW fixtures

Color Test

1: Color Change automatically changes colors for R/RG/RGB/RGBW Fitting



Assign DMX Addresses to Lights



3.DMX Start address for auto addressing. Example:

For DMX flexible strip.10Pixels per meter, RGB Color, if you set start address0001, then address will be 0001 0002 0003,0004 0005,0006......automatically Remember to press "OK&Apply" to confirm your setting.

2: Static Color

Use the fader for each color channel separately to adjust the color. The color mixing and the final color will be shown.



-85-



12-24 VDC























Dimension





DMX Splitter/Booster

DD-8WM

8 way DMX Splitter/Booster.

Isolated DMX Input/Outputs.

DD-8WM splitter is a 8-output DMX splitter with DMX pass-through supporting bi-directional communications for addressing and DMX control. This unit takes the incoming DMX signal and splits the signal into 8 separate output channels.

All 8 output ports have independent output driver to boost the DMX signal. Can be controlled from 512 to 8x512 channels.

Models	DD-8WM
Electrical	
Input Voltage	DC12-24V
Power Consumption	4.5W
Control	
Protocols	DMX512 Control
Power/Data Output	Eight 3-pin terminal sockets
DMX Inputs	1
DMX Thru Link	1
DMX Outputs	8
Physical	
Material	Aluminium
Finish Color	Powder coating, Black
Connector	Compression screw terminals
Mounting	Surface mount
Dimensions (L X W X H)	216×110×21mm